ENTERPRISE INDUSTRIES

eMineral

SUMMIT

FIRE PERFORMANCE | 100% ASBESTOS-FREE | 25 YEAR WARRANTY

Material	Mineral fibre	**Colours**	
Surface	Fleece face	**Environment**	ISO 14001 and ISO 9001
Pattern	Non directional pattern design	**Fire Rating**	NCC GROUP 1 (ISO 9705:2016)
Face Finish		**Performance**	Thickness 19mm; NRC 0.70; CAC 40; LRV 0.90; RH 99

Size Guide

Note: more module and size options available.

Enterprise 100
Two-Way Top Hat Grid

Module	Length	Width	C Spline
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


Enterprise 130
One-Way Grid

Module	Length	Width	C Spline
1200mm	1188mm	600mm max.	25mm
1350mm	1338mm	450mm max.	25mm / 35mm
1500mm	1488mm	500mm max.	25mm / 35mm


Enterprise 120 / 160
T Bar Grid

Module	Length	Width	T Bar
1200x600mm	1195mm	595mm	15mm / 24mm
600x600mm	595mm	595mm	


Edge Details




Top Hat grid
with c-spline edge
Ref: CS




Top Hat grid
with square edge
Ref: SQ



T Bar grid
with square edge
Ref: SQ



15mm T Bar grid
with tegular edge
Ref: TG15



24mm T Bar grid
with tegular edge
Ref: TG24