

SIROCCO



RECYCLED
CONTENT




FIRE
PERFORMANCE



CERTIFIED
BIO-SOLUBLE





100%
ASBESTOS-FREE



25 YEAR
WARRANTY

Material	Mineral fibre
Surface	Sand textured face
Pattern	Non directional pattern design
Face Finish	

Colours	 															
Environment	ISO 14001 and ISO 9001															
Recycled %	60% recycled content															
Fire Rating	NCC GROUP 1 (ISO 9705:2016)															
Performance	<table border="1"> <thead> <tr> <th>Thickness</th> <th>NRC</th> <th>CAC</th> <th>LRV</th> <th>RH</th> </tr> </thead> <tbody> <tr> <td>15mm</td> <td>0.50</td> <td>35</td> <td>0.86</td> <td>99</td> </tr> <tr> <td>19mm</td> <td>0.55</td> <td>40</td> <td>0.86</td> <td>99</td> </tr> </tbody> </table>	Thickness	NRC	CAC	LRV	RH	15mm	0.50	35	0.86	99	19mm	0.55	40	0.86	99
Thickness	NRC	CAC	LRV	RH												
15mm	0.50	35	0.86	99												
19mm	0.55	40	0.86	99												

Size Guide

Note: more module and size options available.


Enterprise 100
Two-Way Top Hat Grid

Module	Length	Width	C Spline
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


Module	Length	Width	C Spline
Enterprise 130 One-Way Grid	1200mm	600mm max.	25mm
	1350mm	450mm max.	25mm / 35mm
	1500mm	500mm max.	25mm / 35mm

Module	Length	Width	T Bar
Enterprise 120 / 160 T Bar Grid	1200x600mm	1195mm	595mm
	600x600mm	595mm	595mm


Edge Details




Top Hat grid
with c-spline edge
Ref: CS



Top Hat grid
with square edge
Ref: SQ



T Bar grid
with square edge
Ref: SQ



15mm T Bar grid
with tegular edge
Ref: TG15



24mm T Bar grid
with tegular edge
Ref: TG24